



PART OF YOUR BUSINESS

# TORQUE EXCELLENT PAG OIL FLUID

Rotary Screw Compressor Lubricant

Edmac Part Number: 3004010068 (20L)

## APPLICATIONS:

TORQUE EXCELLENT PAG FLUID OIL is developed from a unique premium blend of polyalkylene glycol (PAG) and pentaerythritol esters, which together form an exceptional coolant and act to reduce oxidation and deposit formation. These Coolants offer excellent heat transfer properties, long life, high flash points, low evaporation, low volatility, and excellent hydrolytic stability. They do not form varnish deposits like petroleum or PAO oils. TORQUE EXCELLENT PAG FLUID OIL are the generic alternatives to Sullube® 32 and give the equivalent service life of 8,000 hours in rotary screw compressors.

## TYPICAL INDUSTRIAL APPLICATIONS:

- Rotary Screw Compressors

## PERFORMANCE BENEFITS:

- 100% synthetic
- Wide temperature range
- Eliminates deposit formation
- Cost effective
- Eliminates seasonal oil changes
- Polyalkylene glycol/pentaerythritol ester blend
- Extended oil change intervals
- High flash points mean reduced fire hazards
- Waste disposal is minimized due to longer life

TYPICAL PROPERTIES	TEST METHOD	TORQUE EXCELLENT PAG OIL FLUID
ISO Grade	ASTM D2422	32/46
Viscosity @ 40°C,cSt	ASTM D445	40
Viscosity @ 100°C,cSt	ASTM D445	8.3
Viscosity Index	ASTM D2270	188
Flash Point, °C/°F	ASTM D92	265/509
Pour Point, °C/°F	ASTM D97	-48/-55
Auto-ignition, °C	ASTM E659	>390
Foaming Sequences I, II, III	ASTM D892	< 10/0
Color	Visual	Green
Specific Gravity	ASTM D4052	0.99

Sullube 32® is a registered trademark of Sullair.