

Hydrovane FluidForce Vane Warranty Lubricant

VAWO2000-1GT; VAWO2000-5GT; VAWO2000-20GT; VAWO2000-209GT

- Long life
- Improved Efficiency

Premium Rotary Air Compressor Oil

FluidForce Vane 2000 hr Warranty Lubricant (VAWO2000-xxGT) is a premium quality air compressor lubricant designed to deliver high performance lubrication of rotary sliding vane air compressors. It uses an advanced additive system to provide excellent protection and performance for compressors running at up to 10 bar and 100°C discharge temperatures with lubrication maintenance intervals of up to 2000 hours.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Long oil life - Maintenance saving**

FluidForce Vane 2000 hr Warranty Lubricant is capable of providing oil maintenance intervals of up to 2000 hours even when operating at maximum discharge temperatures of up to 100 °C.

It is formulated to help:

- Resist formation of carbon deposits in sliding vane slots in vane compressors
- Resist formation of deposits on rotating components in screw compressors
- Resist thermal breakdown and deposit formation to maintain excellent internal surface cleanliness particularly in oil/air separator and coalescer systems.
- Exact oil maintenance interval will depend on intake air quality, duty cycle and ambient conditions. For hot and humid type climates as found in the Asian and Pacific regions, a reduced oil drain period is recommended (consult CompAir recommendations)

- **Outstanding wear protection**

With many years of successful application, FluidForce Vane 2000 hr Warranty Lubricant helps provide effective protection of internal metal surfaces from corrosion and wear.

It contains an advanced ashless anti-wear system to help prolong the life of critical parts such as bearings and gears.

- **Maintaining system efficiency**

Air release and prevention of foaming are critical performance characteristics in a compressor oil, ensuring reliable start-up and continuous compressed air availability.

FluidForce Vane 2000 hr Warranty Lubricant is designed to provide rapid air release without excessive foaming to give trouble-free operation even under cycling conditions.

In addition, FluidForce Vane 2000 hr Warranty Lubricant has excellent water separation properties to help ensure continuous efficient operation of the compressor even in the presence of water.

Main Applications



- **Rotary sliding vane air compressors**

Suitable for oil flooded or oil injected vane compressors, operating at pressures of up to 10 bar and with air discharge temperatures of up to 100°C.

- **Screw air compressors**

Suitable for oil flooded or oil injected, single or two-stage rotary compressors, operating at pressures of up to 20 bar and with air discharge temperatures of up to 100°C.

Specifications, Approvals & Recommendations

- **ISO 6743-3A-DAJ**

For a full listing of equipment approvals and recommendations, please consult your local CompAir Technical Helpdesk.

Compatibility & Miscibility

- **Seal Compatibility**

FluidForce Vane 2000 hr Warranty Lubricant oils are compatible with seal materials specified for use with mineral oils.

Typical Physical Characteristics

Properties			Method	FluidForce Vane Warranty VAWO-GT
ISO Viscosity Grade			ISO 3448	68
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	68
Kinematic Viscosity	@100°C	mm ² /s	ASTM D445	8.9
Density	@15°C	kg/m ³	ASTM D1298	873
Flash Point (COC)			ASTM D92	248
Air Release			ASTM D3427	5
RPI/OT			ASTM D2272	700
FZG Test			CEC-L-07-A-95	11
Pour Point			ASTM D97	-30
Water Separability	@54°C	mins	ASTM D1401	15

These characteristics are typical of current production. Whilst future production will conform to Hydrovane's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

FluidForce Vane 2000 hr Warranty Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from repsnet.support

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional information

- **Advice**

Advice on applications not covered here may be obtained from your Hydrovane representative.

Viscosity – Temperature Diagram for FluidForce Vane 2000 hr Warranty Lubricant VAWO2000-xxGT

