



PART OF YOUR BUSINESS

# TORQUE FOODGRADE ISO 46

## FOODGRADE COMPRESSOR LUBRICANT

Edmac TORQUE Foodgrade is designed for oil free rotary screw, reciprocating, and rotary vane foodgrade compressor applications. This high-performance lubricant is formulated with high-quality synthetic polyalphaolefin (PAO) base stock and a premium additive package. Features of TORQUE Foodgrade include **excellent thermal and oxidative stability**, thus mini-mizing deposit formation and corrosion. This premium lubricant has **low volatility** and is compatible with mineral oils and equipment designed for use with mineral oils. Edmac TORQUE Foodgrade is **NSF H1 registered** and complies with FDA 21 CFR 178.3570 - lubricants with incidental food contact. It is non-toxic, non-hazardous, and contains no heavy metals.

### Product Details

<b>Part Numbers</b>	3004002751 (5L),
	3004010023 (20L),
	3004010070 (209L)

### Product Compatibility

<b>Kaeser</b>	FG-460
<b>CompAir</b>	SCFG-4000
<b>Boge</b>	Foodlube H1
<b>Almig</b>	Geralyn SF46
<b>Gardner Denver</b>	AEON 6000 FG
<b>Ingersoll Rand</b>	SSR H-1 / Ultra FG

### Features

- Excellent thermal stability
- Excellent oxidative stability
- Corrosion protection
- Low volatility
- NSF H1 registered



PART OF YOUR BUSINESS

## Typical Properties

Properties	Method	TORQUE FOODGRADE ISO 46
<b>ISO Grade</b>	D2422	46
<b>Viscosity</b> @ 40°C, cSt	D445	40,91
<b>Viscosity</b> @ 100°C, cSt	D445	7,32
<b>Viscosity Index</b>	D2270	145
<b>Density</b> g/mL @ 15,6°C	D4052	0,8327
<b>Flash Point</b> , °C	D92	252
<b>Fire Point</b>	D92	256
<b>Pour Point</b> , °C	D97	-43
<b>Copper Strip Corrosion</b>	D130	A1
<b>Air Release</b> , minutes	D3427	0,1

\* These values are not intended for use in preparing specifications

If you require any further information, please contact your Edmac salesperson or [sales.edmac@edmac.eu](mailto:sales.edmac@edmac.eu) .